



# LED FIXTURE SPECIFICATION

MODEL # **CGP**




|               |  |      |  |
|---------------|--|------|--|
| FINAL MODEL # |  |      |  |
| PROJECT       |  |      |  |
| TYPE          |  | AREA |  |
| NOTES         |  |      |  |

## STANDARD FEATURES: SCONCE INDOOR/OUTDOOR

Fixture thermally tested to ensure longevity  
 Maximum light distribution throughout lens  
 Over current/voltage short circuit protection  
 UL and/or CSA Compliant Listed  
 Constant Current Design

| FIXTURE                            | LED ENGINE   |
|------------------------------------|--|
| <b>BASE</b> CR Steel Construction  | <b>LG/NICHIA/SAMSUNG, LED CHIPS</b>  |
| <b>FINISH</b> Architectural Bronze | <b>LUMENS PER WATT</b> AVG 100-120 @Module Efficacy                                |
| <b>LENS</b> Frosted Opal Glass     | <b>KELVIN</b> 27K 30K 35K 40K 50K <b>CRI</b> 80+                                   |
| <b>LOCATION</b> Wet                | <b>DRIVER</b> 120 VOLTS 50/60Hz  |
| <b>COMPLIANT</b>                   | <b>POWER FACTOR</b> High   |
| <b>LIFE HOURS</b> 50,000           | <b>TRIAC OR ELECTRONIC</b><br>Low Voltage Dimming Down To 5% With Wall Box Dimmers |
| <b>WARRANTY</b> Limited 5 Years    | <b>TESTED</b> LM80 and LM82  |



### LED LIGHT SOURCE OPTIONS\* ORDERING INFORMATION:

|             |               |           |
|-------------|---------------|-----------|
| WATTAGE: 12 | KELVIN: 3000k | SIZE: 5x2 |
| WATTAGE:    | KELVIN:       | SIZE:     |

| SIZE OPTIONS             |
|--------------------------|
| W6 <sup>1/2</sup> H10 D4 |

| SYSTEM WATTAGE   | 2700K WARM WHITE | 3000K SOFT WHITE | 3500K NEUTRAL | 4000K COOL WHITE | 5000K DAYLIGHT | LEGACY EQUIVALENT |
|------------------|------------------|------------------|---------------|------------------|----------------|-------------------|
| 10/12 DRIVERLESS |                  | 1000/1000        |               | 1000/1050        |                | CFL 13            |
| 14/15 DRIVERLESS |                  | 1350/1500        |               | 1400/1500        |                | CFL 2 x 13        |
| 22/24 DRIVERLESS |                  | 1850/2400        |               | 1900/2500        |                | CFL 3 x 13        |
| 10               | 1060             | 1100             | 1160          | 1175             | 1250           | CFL 18            |
| 12               | 1265             | 1360             | 1405          | 1460             | 1560           | CFL 2 x 13        |
| 16               | 1650             | 1700             | 1720          | 1750             | 1800           | CFL 2 x 18        |
| 20               | 2100             | 2140             | 2180          | 2200             | 2250           | CFL 2 x 26        |
| 24               | 2570             | 2740             | 2830          | 2950             | 3150           | CFL 2 x 32        |

\*MORE OPTIONS AVAILABLE UPON REQUEST

## SPECIAL OPTIONS (please specify if applicable)

EXAMPLE

|             |             |           |                  |                |
|-------------|-------------|-----------|------------------|----------------|
| DRIVER: DVD | FINISH: FCU | LENS: LCU | ACCESSORIES: FUS | TECHNOLOGY: CT |
| DRIVER:     | FINISH:     | LENS:     | ACCESSORIES:     | TECHNOLOGY:    |

| DRIVER  | FINISH  | LENS                                | ACCESSORIES   | TECHNOLOGY   |
|---|---|-------------------------------------|---|--|
| <input type="checkbox"/> DV 120/277 (Non Dimmable)<br><input type="checkbox"/> DVD 120/277 (0-10v Dimmable) | <input type="checkbox"/> FB Black<br><input type="checkbox"/> FBR Bronzestone<br><input type="checkbox"/> FCU Custom Any RAL Finish<br><input type="checkbox"/> FSN Satin Nickel<br><input type="checkbox"/> FW White | <input type="checkbox"/> LCU Custom | <input type="checkbox"/> BBX Back Box (Conduit Holes Optional)<br><input type="checkbox"/> FUS Fused<br><input type="checkbox"/> IB Individually Boxed<br><input type="checkbox"/> PCH Pull Chain<br><input type="checkbox"/> PS Pin Switch<br><input type="checkbox"/> SRP Surge Protector | <input type="checkbox"/> CT LED Color Tuning<br><input type="checkbox"/> EMG Emergency (Any Lumens Package)<br><input type="checkbox"/> EMGR Emergency Remote<br><input type="checkbox"/> OS Occupancy Sensor On/Off<br><input type="checkbox"/> OSCD Occupancy Sensor Step Dimming<br><input type="checkbox"/> TP Tamper Proof Screws |

### ASL LIGHTING

25 TWELFTH ST. BROOKLYN, NY 11215-3820 | EMAIL: INFO@ASLLIGHTING.COM | WWW.ASLLIGHTING.COM

TOLL FREE: P 800-369-1101 F 800-552-3465 | LOCAL: P 718-369-1100 F 718-369-1105

Specifications and dimensions are subject to change without notice / Consult your ASL lighting representative.

© Copyright 2016 By American Scientific Lighting Corporation. All rights reserved.

