



LED FIXTURE SPECIFICATION

MODEL # **VWF**




| | | | |
|---------------|--|------|--|
| FINAL MODEL # | | | |
| PROJECT | | | |
| TYPE | | AREA | |
| NOTES | | | |

STANDARD FEATURES: SCONCE INDOOR/OUTDOOR

Fixture thermally tested to ensure longevity
 Maximum light distribution throughout lens
 Over current/voltage short circuit protection
 UL and/or CSA Compliant Listed
 Constant Current Design

| FIXTURE | LED ENGINE |
|------------------------------------|------------------------------------------------------|
| BASE CR Steel Construction | LG/NICHIA/SAMSUNG, LED CHIPS |
| FINISH Architectural Bronze | LUMENS PER WATT AVG 100-120 @Module Efficacy |
| LENS Frosted Opal Glass | KELVIN 27K 30K 35K 40K 50K CRI 80+ |
| LOCATION Wet | DRIVER 120 VOLTS 50/60Hz |
| COMPLIANT | POWER FACTOR High |
| LIFE HOURS 50,000 | TRIAC OR ELECTRONIC |
| WARRANTY Limited 5 Years | Low Voltage Dimming Down To 5% With Wall Box Dimmers |
| | TESTED LM80 and LM82 |



LED LIGHT SOURCE OPTIONS* ORDERING INFORMATION:

| | | |
|-------------|---------------|-----------|
| WATTAGE: 12 | KELVIN: 3000k | SIZE: 5x2 |
| WATTAGE: | KELVIN: | SIZE: |

| SIZE OPTIONS | | |
|-------------------|-----|----|
| W6 ^{1/2} | H10 | D4 |

| SYSTEM WATTAGE | 2700K WARM WHITE | 3000K SOFT WHITE | 3500K NEUTRAL | 4000K COOL WHITE | 5000K DAYLIGHT | LEGACY EQUIVALENT |
|------------------|------------------|------------------|---------------|------------------|----------------|-------------------|
| 10/12 DRIVERLESS | | 1000/1000 | | 1000/1050 | | CFL 13 |
| 14/15 DRIVERLESS | | 1350/1500 | | 1400/1500 | | CFL 2 x 13 |
| 22/24 DRIVERLESS | | 1850/2400 | | 1900/2500 | | CFL 3 x 13 |
| 10 | 1060 | 1100 | 1160 | 1175 | 1250 | CFL 18 |
| 12 | 1265 | 1360 | 1405 | 1460 | 1560 | CFL 2 x 13 |
| 16 | 1650 | 1700 | 1720 | 1750 | 1800 | CFL 2 x 18 |
| 20 | 2100 | 2140 | 2180 | 2200 | 2250 | CFL 2 x 26 |
| 24 | 2570 | 2740 | 2830 | 2950 | 3150 | CFL 2 x 32 |

*MORE OPTIONS AVAILABLE UPON REQUEST

SPECIAL OPTIONS (please specify if applicable)

EXAMPLE

| | | | | |
|-------------|-------------|-----------|------------------|----------------|
| DRIVER: DVD | FINISH: FCU | LENS: LCU | ACCESSORIES: FUS | TECHNOLOGY: CT |
| DRIVER: | FINISH: | LENS: | ACCESSORIES: | TECHNOLOGY: |

| DRIVER | FINISH | LENS | ACCESSORIES | TECHNOLOGY |
|-------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/> DV 120/277 (Non Dimmable) <input type="checkbox"/> DVD 120/277 (0-10v Dimmable) | <input type="checkbox"/> FB Black <input type="checkbox"/> FBR Bronzestone <input type="checkbox"/> FCU Custom Any RAL Finish <input type="checkbox"/> FSN Satin Nickel <input type="checkbox"/> FW White | <input type="checkbox"/> LCU Custom | <input type="checkbox"/> BBX Back Box (Conduit Holes Optional) <input type="checkbox"/> FUS Fused <input type="checkbox"/> IB Individually Boxed <input type="checkbox"/> PCH Pull Chain <input type="checkbox"/> PS Pin Switch <input type="checkbox"/> SRP Surge Protector | <input type="checkbox"/> CT LED Color Tuning <input type="checkbox"/> EMG Emergency (Any Lumens Package) <input type="checkbox"/> EMGR Emergency Remote <input type="checkbox"/> OS Occupancy Sensor On/Off <input type="checkbox"/> OSCD Occupancy Sensor Step Dimming <input type="checkbox"/> TP Tamper Proof Screws |

ASL LIGHTING

25 TWELFTH ST. BROOKLYN, NY 11215-3820 | EMAIL: INFO@ASLLIGHTING.COM | WWW.ASLLIGHTING.COM

TOLL FREE: P 800-369-1101 F 800-552-3465 | LOCAL: P 718-369-1100 F 718-369-1105

Specifications and dimensions are subject to change without notice / Consult your ASL lighting representative.

© Copyright 2016 By American Scientific Lighting Corporation. All rights reserved.

