



# Fixture specification

MODEL # : **CTB**  
 STYLE / WATTAGE / KELVIN / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE

PROJECT : \_\_\_\_\_ TYPE : \_\_\_\_\_ NOTE : \_\_\_\_\_



SIZE  
 W4" H4" D5-3/4"

**FIXTURE FEATURES**

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

**BASE:** ALUMINUM  
 MOUNTS OVER ELECTRICAL BOX

**FINISH:** BRUSHED ALUMINUM  
**LENS:** ACRYLIC  
 UV STABILIZED  
 NON-YELLOWING

**FEATURE:** UP & DOWN LIGHT  
**INPUT VOLTAGE:** 120 - 277V;50/60Hz  
**INPUT WATTAGE:** 9W  
**KELVIN:** 3000  
**CRI:** 81  
**LUMEN:** 630  
**COMPLIANCE:** UL AND/OR CSA LISTED  
 WET LOCATION

**SPECIAL OPTIONS**

- DRIVER
- DV 120 / 277 (NON DIMMABLE)
  - DVD 120 / 277 (0-10V DIMMABLE)
  - EMG EMERGENCY
  - EMGR EMERGENCY REMOTE

FINISH  
 FCU CUSTOM (ANY FINISH AVAILABLE)

COMPLIANCE  
 ES ENERGY STAR (WHEN SPECIFIED)  
 MIA MADE IN AMERICA

ACCESSORIES  
 EPC EXTERNAL PHOTOCELL  
 FUS FUSE  
 IB INDIVIDUAL BOX  
 IPC INTERNAL PHOTOCELL  
 TP TAMPER SCREWS

For Additional Accessories and Options Visit [www.aslighting.com](http://www.aslighting.com)

ASL  
 25 Twelfth Street  
 Brooklyn, NY 11215-3820

Toll Free  
 Phone: 800-369-1101  
 Fax: 800-552-3465



Local  
 Phone: 718-369-1100  
 Fax: 718-369-1105

Online  
 email: [info@aslighting.com](mailto:info@aslighting.com)  
 visit: [www.aslighting.com](http://www.aslighting.com)

© copyright 2016 by American Scientific Lighting Corp. All rights reserved.

**CTB**