



# Fixture Specification

MODEL # : **CTJ**  
 STYLE / WATTAGE / KELVIN / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE

PROJECT : \_\_\_\_\_ TYPE : \_\_\_\_\_ NOTE : \_\_\_\_\_



SIZE  
 W4-1/2" H7" D7"

**FIXTURE FEATURES**

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

**BASE:** STEEL

MOUNTS OVER ELECTRICAL BOX

**FINISH:** BRUSHED NICKEL

**FEATURE:** UP & DOWN LIGHT

INPUT VOLTAGE: 120V; 50/60Hz

INPUT WATTAGE: 8W

KELVIN: 3000

CRI: 81

LUMEN: 500

COMPLIANCE: UL AND/OR CSA LISTED

WET LOCATION

**SPECIAL OPTIONS**

DRIVER

- DV 120 / 277 (NON DIMMABLE)
- DVD 120 / 277 (0-10V DIMMABLE)
- EMG EMERGENCY
- EMGR EMERGENCY REMOTE

FINISH

- FCU CUSTOM (ANY FINISH AVAILABLE)

COMPLIANCE

- ES ENERGY STAR (WHEN SPECIFIED)
- MIA MADE IN AMERICA

ACCESSORIES

- EPC EXTERNAL PHOTOCELL
- FUS FUSE
- IB INDIVIDUAL BOX
- IPC INTERNAL PHOTOCELL
- TP TAMPER SCREWS

For Additional Accessories and Options Visit [www.aslighting.com](http://www.aslighting.com)

ASL  
 25 Twelfth Street  
 Brooklyn, NY 11215-3820

Toll Free  
 Phone: 800-369-1101  
 Fax: 800-552-3465



Local  
 Phone: 718-369-1100  
 Fax: 718-369-1105

Online  
 email: [info@aslighting.com](mailto:info@aslighting.com)  
 visit: [www.aslighting.com](http://www.aslighting.com)

© copyright 2016 by American Scientific Lighting Corp. All rights reserved.

**CTJ**