



Fixture specification

MODEL # : **CTR**
 STYLE / WATTAGE / KELVIN / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE

PROJECT : _____ TYPE : _____ NOTE : _____



SIZE
 W5" H6-1/4" D5"

FIXTURE FEATURES

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

BASE: ALUMINUM
 MOUNTS OVER ELECTRICAL BOX

FINISH: ARCHITECTURAL BRONZE
LENS: ACRYLIC
 UV STABILIZED
 NON-YELLOWING

INPUT VOLTAGE: 120 - 277V;50/60Hz
INPUT WATTAGE: 15W
KELVIN: 3000
CRI: 81
LUMEN: 1050
COMPLIANCE: UL AND/OR CSA LISTED
 WET LOCATION

SPECIAL OPTIONS

- DRIVER
- DV 120 / 277 (NON DIMMABLE)
 - DVD 120 / 277 (0-10V DIMMABLE)
 - EMG EMERGENCY
 - EMGR EMERGENCY REMOTE

- FINISH
- FBA BRUSHED ALUMINUM
 - FCU CUSTOM (ANY FINISH AVAILABLE)

- COMPLIANCE
- ES ENERGY STAR (WHEN SPECIFIED)
 - MIA MADE IN AMERICA

- ACCESSORIES
- EPC EXTERNAL PHOTOCELL
 - FUS FUSE
 - IB INDIVIDUAL BOX
 - IPC INTERNAL PHOTOCELL
 - TP TAMPER SCREWS

For Additional Accessories and Options Visit www.aslighting.com

ASL
 25 Twelfth Street
 Brooklyn, NY 11215-3820

Toll Free
 Phone: 800-369-1101
 Fax: 800-552-3465



Local
 Phone: 718-369-1100
 Fax: 718-369-1105

Online
 email: info@aslighting.com
 visit: www.aslighting.com

© copyright 2016 by American Scientific Lighting Corp. All rights reserved.

CTR