



Fixture specification

MODEL # : **CTS**

STYLE / WATTAGE / KELVIN / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE

PROJECT : _____ TYPE : _____ NOTE : _____



SIZE

W4" H5-1/4" D5"

FIXTURE FEATURES

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

BASE: ALUMINUM

MOUNTS OVER ELECTRICAL BOX

FINISH: ARCHITECTURAL BRONZE

LENS: ACRYLIC
UV STABILIZED
NON-YELLOWING

FEATURE: UP & DOWN LIGHT

INPUT VOLTAGE: 120 - 277V;50/60Hz

INPUT WATTAGE: 9W

KELVIN: 3000

CRI: 81

LUMEN: 315

COMPLIANCE: UL AND/OR CSA LISTED
WET LOCATION

SPECIAL OPTIONS

DRIVER

- DV 120 / 277
(NON DIMMABLE)
- DVD 120 / 277
(0-10V DIMMABLE)
- EMG EMERGENCY
- EMGR EMERGENCY REMOTE

FINISH

- FBA BRUSHED ALUMINUM
- FCU CUSTOM
(ANY FINISH AVAILABLE)

COMPLIANCE

- ES ENERGY STAR
(WHEN SPECIFIED)
- MIA MADE IN AMERICA

ACCESSORIES

- EPC EXTERNAL PHOTOCELL
- FUS FUSE
- IB INDIVIDUAL BOX
- IPC INTERNAL PHOTOCELL
- TP TAMPER SCREWS

For Additional Accessories and Options Visit www.aslighting.com

ASL
25 Twelfth Street
Brooklyn, NY 11215-3820

Toll Free
Phone: 800-369-1101
Fax: 800-552-3465



Local
Phone: 718-369-1100
Fax: 718-369-1105

Online
email: info@aslighting.com
visit: www.aslighting.com

© copyright 2016 by American Scientific Lighting Corp. All rights reserved.

CTS