



Fixture specification

MODEL # : **DSKE**
 STYLE / WATTAGE / KELVIN / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE

PROJECT : _____ TYPE : _____ NOTE : _____



SIZE
 W4-3/4' H7-1/8" D6-7/8'

FIXTURE FEATURES

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

BASE: DIE-CAST ALUMINUM
 MOUNTS OVER ELECTRICAL BOX

FINISH: BRONZE
LENS: ACRYLIC
 UV STABILIZED
 NON-YELLOWING

FEATURE: UP & DOWN LIGHT
INPUT VOLTAGE: 120 - 277V/50/60Hz
INPUT WATTAGE: 26W
KELVIN: 5000
CRI: 75
LUMEN: 1750
COMPLIANCE: UL AND/OR CSA LISTED
 WET LOCATION

SPECIAL OPTIONS

- DRIVER
- DV 120 / 277 (NON DIMMABLE)
 - DVD 120 / 277 (0-10V DIMMABLE)
 - EMG EMERGENCY
 - EMGR EMERGENCY REMOTE

FINISH
 FCU CUSTOM (ANY FINISH AVAILABLE)

COMPLIANCE
 ES ENERGY STAR (WHEN SPECIFIED)
 MIA MADE IN AMERICA

ACCESSORIES
 EPC EXTERNAL PHOTOCELL
 FUS FUSE
 IB INDIVIDUAL BOX
 IPC INTERNAL PHOTOCELL
 TP TAMPER SCREWS

For Additional Accessories and Options Visit www.aslighting.com

ASL
 25 Twelfth Street
 Brooklyn, NY 11215-3820

Toll Free
 Phone: 800-369-1101
 Fax: 800-552-3465



Local
 Phone: 718-369-1100
 Fax: 718-369-1105

Online
 email: info@aslighting.com
 visit: www.aslighting.com

© copyright 2016 by American Scientific Lighting Corp. All rights reserved.

DSKE