



Fixture Specification

MODEL # : **GAF**
 STYLE / WATTAGE / KELVIN / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE

PROJECT : _____ TYPE : _____ NOTE : _____



SIZE
 W15" H8-1/2" D11"

FIXTURE FEATURES

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

BASE: DIE CAST ALUMINUM

MOUNTS OVER ELECTRICAL BOX
 FOUR 1/2" THREADED REMOVABLE PLUGS

FINISH: ARCHITECTURAL BRONZE
LENS: CLEAR BOROSILCATE GLASS

INPUT VOLTAGE: 120-277V; 50/60Hz

INPUT WATTAGE: 74W
KELVIN: 5000
CRI: 70
LUMEN: 6230
POWER FACTOR: 90
COMPLIANCE: UL AND/OR CSA LISTED
 WET LOCATION

SPECIAL OPTIONS

DRIVER

- DV 120 / 277 (NON DIMMABLE)
- DVD 120 / 277 (0-10V DIMMABLE)
- EMG EMERGENCY
- EMGR EMERGENCY REMOTE

FINISH

- FCU CUSTOM (ANY FINISH AVAILABLE)

COMPLIANCE

- ES ENERGY STAR (WHEN SPECIFIED)
- MIA MADE IN AMERICA

ACCESSORIES

- FUS FUSE
- IB INDIVIDUAL BOX
- IPC INTERNAL PHOTOCELL
- TP TAMPER SCREWS

FEATURE

- PM 4" SQUARE POLE MOUNTING

For Additional Accessories and Options Visit www.aslighting.com

ASL
 25 Twelfth Street
 Brooklyn, NY 11215-3820

Toll Free
 Phone: 800-369-1101
 Fax: 800-552-3465



Local
 Phone: 718-369-1100
 Fax: 718-369-1105

Online
 email: info@aslighting.com
 visit: www.aslighting.com

© copyright 2016 by American Scientific Lighting Corp. All rights reserved.

