



# Fixture Specification

MODEL # : **WPU-D8**

STYLE / WATTAGE / KELVIN / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE

PROJECT : \_\_\_\_\_ TYPE : \_\_\_\_\_ NOTE : \_\_\_\_\_



SIZE

W5-5/8" H3-3/8" D7-3/4"

**FIXTURE FEATURES**

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

BASE: DIE-CAST ALUMINUM

MOUNTS OVER ELECTRICAL BOX OR TO STRUCTURE FOR SURFACE CONDUIT

THREE 1/2" THREADED APERTURES

FINISH: BRONZE

LENS: POLYCARBONATE  
UV STABILIZED  
NON-YELLOWING

INPUT VOLTAGE: 120-277V;50/60Hz

INPUT WATTAGE: 60w

KELVIN: 5000

CRI: 70

LUMEN: 4460

COMPLIANCE: UL AND/OR CSA LISTED  
WET LOCATION

**SPECIAL OPTIONS**

DRIVER

- DV 120 / 277 (NON DIMMABLE)
- DVD 120 / 277 (0-10V DIMMABLE)
- EMG EMERGENCY
- EMGR EMERGENCY REMOTE

FINISH

- FCU CUSTOM (ANY FINISH AVAILABLE)

COMPLIANCE

- ES ENERGY STAR (WHEN SPECIFIED)
- MIA MADE IN AMERICA

ACCESSORIES

- EPC EXTERNAL PHOTOCELL
- FUS FUSE
- IB INDIVIDUAL BOX
- IPC INTERNAL PHOTOCELL
- OC OCCUPANCY SENSOR
- SP SURGE PROTECTOR
- TP TAMPER SCREWS

For Additional Accessories and Options Visit [www.aslighting.com](http://www.aslighting.com)

ASL  
25 Twelfth Street  
Brooklyn, NY 11215-3820

Toll Free  
Phone: 800-369-1101  
Fax: 800-552-3465



Local  
Phone: 718-369-1100  
Fax: 718-369-1105

Online  
email: [info@aslighting.com](mailto:info@aslighting.com)  
visit: [www.aslighting.com](http://www.aslighting.com)

© copyright 2016 by American Scientific Lighting Corp. All rights reserved.

**WPU-D8**